Products

Product descriptions, basic applications and further help links.

Picture	Reference	Name	Description	Size	Weight	Colours	Packaging	Application	Technical Support online or through sales office Roadcraft or Fleming
	1	301/290 roadstud base only.	Roadstud: Cast metal grey iron base without reflector. Requires 290 reflector.	Width: 142mm Length: 180mm Depth: 41mm	2.8 kgs each.	Cast Grey.	400 per pallet.	Installed using truck mounted milling machine.	www.roadstuds.co.uk
	2	301/190 roadstud base only.	Roadstud: Cast metal grey iron base without reflector. Requires 190 reflector.	Width: 142mm Length: 180mm Depth: 41mm	2.6 kgs each.	Cast Grey.	400 per pallet.	Installed using truck mounted milling machine.	www.roadstuds.co.uk
	3	3M 290 roadstud.	Roadstud reflector can be surface mounted or inset into 301 casting.	Width: 101mm Length: 89mm Depth: 16mm	8 kgs per carton.	White, red, green, yellow body and reflectors configured uni or duo reflective.	100 per carton.	Surface mounted applied or as an insert reflector for 301 casting.	www.roadstuds.co.uk
	4	3M 190 roadstud.	Roadstud reflector insert for 301 casting. Durable polycarbonate body is impact and weather resistant. Microprismatic optics provide excellent wet and dry reflectance.	Width: 97mm Length: 45mm Depth: 10mm	5.5 kgs carton.	Black polycarbonate body reflectors red, white yellow, green configured uni or duo reflective.	100 per carton.	As an insert reflector for 301 casting only.	www.roadstuds.co.uk
	5	3M 590 roadstud.	Depressible roadstud insert for use in base component.	Width: 97mm Length: 80mm Depth: 50mm	10 kgs per pack.	White, red, green and yellow reflectors configured uni or duo reflective.	50 per polythene bag.	Requires base component, manually installed.	www.roadstuds.co.uk
	6	Safemark temporary roadstud - Hot melt type.	Temporary roadstud used in traffic delineation.	Width: 97mm Length: 57mm Depth: 15mm	11.5 kgs per sack.	Fluorescent yellow body and reflectors white, red, green, yellow configured uni or duo reflective.	300 per poly sack.	Hot Melt adhesive application. Manually installed.	www.roadstuds.co.uk
	7	Safemark temporary roadstud - Self adhesive type.	Temporary roadstud used in traffic delineation.	Width: 97mm Length: 57mm Depth: 15mm	10 kgs per carton.	Fluorescent yellow body and reflectors white, red, green, yellow configured uni or duo reflective.	200 per carton.	Pre-heating of carriageway, manually installed.	www.roadstuds.co.uk
	8	Pedestrian Crossing Studs - Aluminium - Plain or Profiled.	Non reflective crossing studs used to delineate pedestrian crossings.	100mm Square Top Fishtail Shank 76mm	22.0 kgs per sack.	Silver Aluminium - Non Reflective.	100 per polypropylene sack.	Drill a hole 32mm diameter to a depth of 80mm, hot melt adhesive applied.	www.roadstuds.co.uk
	9	Pedestrian Crossing Studs - Stainless Steel - Plain.	Non reflective crossing studs used to delineate pedestrian crossings.	100mm Square Top Chisel Shank 76mm	26 kgs per sack.	Silver stainless. Non reflective.	50 per polypropylene sack.	Drill a hole 32mm diameter to a depth of 80mm, hot melt adhesive applied.	www.roadstuds.co.uk

The above chart gives a basic description of each individual product sufficient to allow a measure of customer conformity.
Further information obtained by calling: Roadcraft England and Wales +44 (0)1934 825 850 Fleming Scotland: +44 (0)141 881 8155 Fleming North East England: +44 (0)191 214 5454 or visit our website www.roadstuds.co.uk